

Decorative textured finish

Product description

Based on acrylic copolymers containing special fillers and pigments which are not affected by the different environmental conditions.

Recommended use:

Suitable for exterior and interior work. It is mainly used for decoration, it gives many textured finishes.

Physical properties

Colour	:	white or colored.
Solid content	:	80% \pm 1.
Coverage power	:	1-2 m ² /kg. According to the thickness required.
Sp. Gravity	:	1.37
Viscosity	:	non sag paste.
Surface dry	:	30 min.
Hard dry	:	8 hours.
Thinner	:	water.

Surface preparation

Surface should be clean. Dry and free from any contaminations.

The surface should be treated by suitable methods.

Application methods:

It is usually applied directly on concrete, plaster and woodwork.

It can be applied by:

- Spray : use airless spray
- Brush : recommended for small area .and care must be taken to achieve the specified dry film thickness.
- Roller : may be used, when using roller application care must be taken to achieve the specified dry film thickness.

Storage:

Product must be stored in accordance with neutral regulations. And the storage conditions are to keep the containers in a dry, cool, good ventilated, and away from source of heat and ignition.

Packing

Upon client request

Health and safety:

Please observe the precautionary notices displayed on the container. Use under well-ventilated conditions. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Flammable product to be used and stored away from heat sources and naked flames. Do not smoke when using, avoid prolonged inhalation. Observe the general rules governing the use of solvents.

Use protective goggles and gloves, work in well ventilated areas with constant renewal of the air.