

Fast dry enamel

Product description:

Industrial, fast drying synthetic enamel, with excellent properties of hardness and adhesion to the surfaces.

RECOMMENDED USES:

Particularly recommended for painting toys, industrial machines (tractors, earth-moving equipment, drums, pipe-lines, electricity towers, etc...).

Physical properties

| | | |
|----------------|---|------------------------|
| Colour | : | as Client request. |
| Sp. Gravity | : | 1.3 g/Cm ³ |
| Viscosity | : | 200 sec (ford cup). |
| Surface dry | : | 20-25 min |
| Hard dry | : | 6 hours. |
| Covering power | : | 10 m ² /Kg. |

Surface preparation

Surface should be clean, dry and free from any contaminations. The surface should be treated by suitable methods to allow coated surfaces receiving primer coat to be capable of maximum adhesion.

Application methods:

Applied only by :

Spray; use airless spray.

Recommended substrate conditions:

Steel; blast cleaned to SIS-Sa 21/2.

Galvanized steel and aluminum; dry and free from salts and sufficiently roughened.

Storage:

Product must be stored in accordance with rural regulations. And the storage conditions are to keep the containers in a dry, cool, well- ventilated areas, and away from source of heat and ignition.

Packing

To be agreed upon with client.

Ready packing:

Kgs 4.00 cans

Kgs 20.00 cans

Health and safety:

Please observe the precautionary notices displayed on the container. Use under well-ventilated conditions. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Flammable product to be used and stored away from heat sources and naked flames. Do not smoke when using, avoid prolonged inhalation. Observe the general rules governing the use of solvents.

Use protective goggles and gloves, work in well ventilated areas with constant renewal of the air.