

## **Cibccr Acrocoat Plast**

### **Product description**

High Quality washable acrylic copolymer emulsion paint, easy to apply. High spreading capacity. Washable by water and soap without any effect on the prosperities of the paint. Completely resist yellowing.

### **Recommended use:**

For buildings fronts, interior and exterior walls.

### **Physical properties**

Colour	:	white
Solid content	:	60%.
Coverage power	:	6-8 m <sup>2</sup> /kg. For one coat.
Sp. Gravity	:	1.4 g/cm <sup>3</sup> .
Surface dry	:	20 min.
Hard dry	:	6 hours.
Thinner	:	water (10%first coat, 5%second coat).

### **Surface preparation**

Surface should be clean. Dry and free from any contaminations.  
The surface should be treated by suitable methods.

### **Application methods:**

Apply a highly diluted first coat and controlled dilution finishing coat. Brush or roller can be used.

### **Storage:**

Product must be stored in accordance with neutral regulations. And the storage conditions are to keep the containers in a dry, cool, good ventilated, and away from source of heat and ignition.

### **Packing**

Upon client request

### **Health and safety:**

Please observe the precautionary notices displayed on the container. Use under well-ventilated conditions. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Flammable product to be used and stored away from heat sources and naked flames. Do not smoke when using, avoid prolonged inhalation. Observe the general rules governing the use of solvents.

Use protective goggles and gloves, work in well ventilated areas with constant renewal of the air.