

NC Varnish Nitrovane

Product description

Highly transparent cellulose varnish, based on high nitrocellulose and other resins. It produces a highly glossy and smooth surface, free from cracking and wrinkling. Outstanding scratch and abrasion resistance.

Recommended uses

A final top coat for all wood surfaces and furniture.

Physical properties

Colour	:	transparent.
Apperance	:	Gloss or matt
Viscosity	:	240 sec (ford cup)
Surface dry	:	30min
Hard dry	:	3 hours
Spreading capacity	:	8-10 m2/Kg.

Surface preparation:

Surface should be clean, dry and free from any contaminations.
The surface should be treated by suitable methods.

Application methods

Spray	:	use airless spray
Brush	:	recommended for small area .and care must be taken to achieve the specified dry film thickness.

Storage:

Product must be stored in accordance with neutral regulations. And the storage conditions are to keep the containers in a dry, cool, well- ventilated, and away from source of heat and ignition.

Packing

Upon client request.

Health and safety:

Please observe the precautionary notices displayed on the container. Use under well-ventilated conditions. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Flammable product use and stored away from heat sources and naked flames. Do not smoke when using, avoid prolonged inhalation. Observe the general rules governing the use of solvents.

Use protective goggles and gloves, work in well ventilated areas with constant renewal of the air.