

Sealeriano 1010

Product description:

Based on nitrocellulose with high quality hydrocarbon resins and sanding materials, it has an outstanding filling and sanded properties. Easy to apply with high scratch and abrasion resistance.

Recommended uses:

Cibccr sealriano used as sealant for wooden surfaces and as a primer for the top coats.

Physical properties

Colour	:	transparent
Thinner	:	cibccr sealer thinner
Spreading. Capacity	:	8-10 m ² /Kg
Surface dry	:	20 min
Hard dry	:	3 hours

Surface preparation

Surface should be clean, dry and free from any contaminations.
The surface should be treated by suitable methods.

Application methods:

Spray	:	use airless spray
Brush	:	recommended for small area .and care must be taken to achieve the specified dry film thickness.

Storage:

Product must be stored in accordance with neutral regulations. And the storage conditions are to keep the containers in a dry, cool, well-ventilated, and away from source of heat and ignition.

Packing

1 kilogram & 3 kilogram

Health and safety:

Please observe the precautionary notices displayed on the container. Use under well-ventilated conditions. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Flammable product use and stored away from heat sources and naked flames. Do not smoke when using, avoid prolonged inhalation. Observe the general rules governing the use of solvents.

Use protective goggles and gloves, work in well ventilated areas with constant renewal of the air.