

Cibccr Traffic

Product description:

It is based on a combination of special resins and pigments and extenders for traffic road marking . It has an outstanding resistance to rubbing and abrasion also withstands the atmospheric condition, fuels and chemicals.

Recommended uses

For horizontal road sign (unbroken line, broken lines, arrows, boundary lines, inscriptions.). It can be applied to various surfaces such as asphalts, granite, concrete, etc.

Physical properties

Colour	:	white and yellow.
Solid content	:	60%.
Surface dry	:	5 min
Hard dry	:	10-15 min.
Covering power	:	various according to the surface type.

Surface preparation

Surface should be clean, dry and free from any contaminations. The surface should be treated by suitable methods to allow coated surfaces receiving primer coat to be capable of maximum adhesion.

Application methods:

- Spray : use airless spray
- Brush : recommended for small area .and care must be taken to achieve the specified dry film thickness.
- Roller : may be used, when using roller application care must be taken to achieve the specified dry film thickness.

The refractive effect is obtained by the carefully controlled addition of top quality glass beads guaranteed resistant to wear with a high refractive index.

Storage:

Product must be stored in accordance with rural regulations. And the storage conditions are to keep the containers in a dry, cool, well- ventilated areas, and away from source of heat and ignition.

Packing

To be agreed upon with client.

Ready packing:

Kgs 4.00 cans

Kgs 20.00 cans

Health And Safety:

Please observe the precautionary notices displayed on the container. Use under well- ventilated conditions. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Flammable product to be used and stored away from heat sources and naked flames. Do not smoke when using, avoid prolonged inhalation. Observe the general rules governing the use of solvents.

Use protective goggles and gloves, work in well ventilated areas with constant renewal of the air.