

# **Cibccr Alkyd varnish**

### **Product description**

Cibccr Alkyd Varnish is a high quality alkyd used for high durability applications, based on special alkyd resins, and additives to protect, providing aesthetic appearance

Main features of Cibccr Alkyd varnish

- -Strong adhesion, hardness.
- -High resistance to scratching and different weather condition.

### Recommended use:

- High recommendation for household furniture such as beds, cabinets, chairs, sofas, doors and frames turned pieces and likes

## **Physical properties**

Colour : transparent varnish.

Touch Dry : 3-4 min.

Hard Dry : 18 hours

Coverage power : 9-11 m<sup>2</sup>/kg.

# Surface preparation

Paint the surface with a Cibccr Nitrocellulose sealer (Sealeriano 1010), then sand it after complete drying to get a smooth surface, and then finish it with two coats of Glossy Varnish.



# شركة سيبكر مصر للبويات والصناعات الكيماوية CIBCR EGYPT For Paints & Chemical Industries

### **Application methods:**

It can be applied by:

Spray : use airless spray

Brush : recommended for small area .and care must be

taken to achieve the specified dry film thickness.

### Storage:

Product must be stored in accordance with neutral regulations. And the storage conditions are to keep the containers in a dry, cool, wellventilated, and away from source of heat and ignition.

# Packging:

Upon client request

Ready Packing: Gallon 4KGs, 20 Kg

# Health and safety:

Please observe the precautionary notices displayed on the container. Use under well- ventilated conditions. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Flammable product use and stored away from heat sources and raked flames. Do not smoke when using, avoid prolonged inhalation. Observe the general rules governing the use of solvents. Use protective goggles and gloves, work in well ventilated areas with constant renewal of the air.