

Cibccr semilac lacquer

Product description:

it a paint which is made from an excellent alkyd resins which gives you a semi gloss finish.

Recommended use:

it is applied on every surface (wood. metal surface and concrete).

Technical information:

Color	:	upon Clint request.
Solid content%	:	60%
Viscosity	:	180 sec according to cup 4 at 25 °C.
Appearance	:	semi gloss.
Film thickness	:	50-70 micron (wet)
	:	35-55 micron (dry)
Application range	:	8:10 m ² /kg for one coat surface.

Application data:

Application method: brush or by airless spray.

Mixing ratio	:	5-10% of total weight.
Drying time	:	2hr (touch dry).
	:	6-8 hr (final dry).

Surface preparation:

the surface must be clean and dry from any contamination (dirt or grease) By suitable methods.

Typical recommended paint system:

Cibccr primer : 50 micron (dry film).

Cibccr Matt enamel : 50 micron (dry film).

Storage & packing:

the product must be stored in national regulations avoiding the sun light and keep it in a good ventilations.

Packing:

upon Clint request.

Health & safety:

Please observe the precautionary notices displayed on the container. Use under well-ventilated conditions. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Flammable product to be used and stored away from heat sources and naked flames. Do not smoke when using, avoid prolonged inhalation. Observe the general rules governing the use of solvents.

Use protective goggles and gloves, work in well ventilated areas with constant renewal of the air.